§761.63

from the same disposal waste stream and with each shipment thereafter. The notice shall state that the PCB bulk product waste may include components containing PCBs at ≥ 50 ppm based on analysis of the waste in the shipment or application of a general knowledge of the waste stream (or similar material) which is known to contain PCBs at those levels, and that the PCB bulk product waste is known or presumed to leach $\geq 10~\mu g/L$ PCBs.

- (5) Any person disposing of PCB bulk product waste must maintain a written record of all sampling and analysis of PCBs or notifications made under this paragraph for 3 years from the date of the waste's generation. The records must be made available to EPA upon request.
- (6) Requirements in subparts C, J, and K of this part do not apply to waste disposed of under paragraph (b) of this section.
- (c) Risk-based disposal approval. (1) Any person wishing to sample or dispose of PCB bulk product waste in a manner other than prescribed in paragraphs (a) or (b) of this section, or store PCB bulk product waste in a manner other than prescribed in §761.65, must apply in writing to the Regional Administrator in the Region where the sampling, disposal, or storage site is located, for sampling, disposal, or storage occurring in a single EPA Region; or to the Director, Office of Resource Conservation and Recovery, for sampling, disposal, or storage occurring in more than one EPA Region. Each application must contain information indicating that, based on technical, environmental, or waste-specific characteristics or considerations. the proposed sampling, disposal, or storage methods or locations will not pose an unreasonable risk or injury to health or the environment. EPA may request other information that it believes necessary to evaluate the application. No person may conduct sampling, disposal, or storage activities under this paragraph prior to obtaining written approval by EPA.
- (2) EPA will issue a written decision on each application for a risk-based sampling, disposal, or storage method for PCB bulk product wastes. EPA will approve such an application if it finds

that the method will not pose an unreasonable risk of injury to health or the environment.

- (d) Disposal as daily landfill cover or roadbed. Bulk product waste described in paragraph (b)(1) of this section may be disposed of:
- (1) As daily landfill cover as long as the daily cover remains in the landfill and is not released or dispersed by wind or other action: or
- (2) Under asphalt as part of a road

[63 FR 35451, June 29, 1998, as amended at 64 FR 33761, June 24, 1999; 72 FR 57239, Oct. 9, 2007; 74 FR 30232, June 25, 2009]

§ 761.63 PCB household waste storage and disposal.

PCB household waste, as defined at §761.3, managed in a facility permitted, licensed, or registered by a State to manage municipal or industrial solid waste, or in a facility with an approval to dispose of PCB bulk product waste under §761.62(c), is not subject to any other requirements of part 761 of this chapter. PCB household waste stored in a unit regulated for storage of PCB waste must not be commingled with PCB waste.

[63 FR 35452, June 29, 1998]

§ 761.64 Disposal of wastes generated as a result of research and development activities authorized under § 761.30(j) and chemical analysis of PCBs.

This section provides disposal requirements for wastes generated during and as a result of research and development authorized under §761.30(j). This section also provides disposal requirements for wastes generated during the chemical analysis of samples containing PCBs under part 761, including §§761.30, 761.60, 761.61, 761.62, and 761.79. For determining the presence of PCBs in samples, chemical analysis includes: sample preparation, sample extraction, extract cleanup, extract concentration, addition of PCB standards, and instrumental analysis.

(a) Portions of samples of a size designated in a chemical extraction and analysis method for PCBs and extracted for purposes of determining the presence of PCBs or concentration of

Environmental Protection Agency

PCBs are unregulated for PCB disposal under this part.

- (b) All other wastes generated during these activities are regulated for disposal based on their concentration at the time of disposal as follows:
- (1) Liquid wastes, including rinse solvents, must be disposed of according to \$761.61(a)(5)(iy).
- (2) Non-liquid wastes must be disposed of in the same manner as non-liquid cleaning materials and personal protective equipment waste according to \$761.61(a)(5)(v)(A).

[63 FR 35452, June 29, 1998]

§ 761.65 Storage for disposal.

This section applies to the storage for disposal of PCBs at concentrations of 50 ppm or greater and PCB Items with PCB concentrations of 50 ppm or greater.

- (a)(1) Storage limitations. Any PCB waste shall be disposed of as required by subpart D of this part within 1-year from the date it was determined to be PCB waste and the decision was made to dispose of it. This date is the date of removal from service for disposal and the point at which the 1-year time frame for disposal begins. PCB/radioactive waste removed from service for disposal is exempt from the 1-year time limit provided that the provisions at paragraphs (a)(2)(ii) and (a)(2)(iii) of this section are followed and the waste is managed in accordance with all other applicable Federal, State, and local laws and regulations for the management of radioactive material.
- (2) One-year extension. Any person storing PCB waste that is subject to the 1-year time limit for storage and disposal in paragraph (a)(1) of this section may provide written notification to the EPA Regional Administrator for the Region in which the PCB waste is stored that their continuing attempts to dispose of or secure disposal for their waste within the 1-year time limit have been unsuccessful. Upon receipt of the notice by the EPA Regional Administrator, the time for disposal is automatically extended for 1 additional year (2 years total) if the following conditions are met:
- (i) The notification is received by the EPA Regional Administrator at least 30 days before the initial 1-year time

limit expires and the notice identifies the storer, the types, volumes, and locations of the waste and the reasons for failure to meet the initial 1-year time limit.

- (ii) A written record documenting all continuing attempts to secure disposal is maintained until the waste is disposed of.
- (iii) The written record required by paragraph (a)(2)(ii) of this section is available for inspection or submission if requested by EPA.
- (iv) Continuing attempts to secure disposal were initiated within 270 days after the time the waste was first subject to the 1-year time limit requirement, as specified in paragraph (a)(1) of this section. Failure to initiate and continue attempts to secure disposal throughout the total time the waste is in storage shall automatically disqualify the notifier from receiving an automatic extension under this section
- (3) Additional extensions. Upon written request, the EPA Regional Administrator for the Region in which the wastes are stored or the appropriate official at EPA Headquarters, may grant additional extensions beyond the 1year extension authorized in paragraph (a)(2) of this section. At the time of the request, the requestor must supply specific justification for the additional extension and indicate what measures the requestor is taking to secure disposal of the waste or indicate why disposal could not be conducted during the period of the prior extension. The EPA Regional Administrator or the appropriate official at EPA Headquarters may require, as a condition to granting any extension under this section, specific actions including, but not limited to, marking, inspection, recordkeeping, or financial assurance to ensure that the waste does not pose an unreasonable risk of injury to health or the environment.
- (4) Storage at an approved facility. Increased time for storage may be granted as a condition of any TSCA PCB storage or disposal approval, by the EPA Regional Administrator for the Region in which the PCBs or PCB Items are to be stored or disposed of, or by the appropriate official at EPA Headquarters, if EPA determines that